

NQD-TPL-20 KIT CONTENTS. INSPECTED BY:_____

BASE PLATE- STANDARD OR JD (**NQD-071** OR **NQD-104**)

DOOR BAR- STANDARD (**NQD-080**)

HANDLE PIVOT- (**NQD-117**) OTR WITH (**HU-12**) HANDLE EXTENSION (SINGLE BEND)

BRACKETS- **(UB-09) 2.687" TALL U BRACKETS INSTALLED.**

HANDLE- (**MINI-21**) MINI FLAT BAR HANDLE

DOOR- **NQD-TPL20**

CENTER DEFLECTOR- STANDARD (**NQD-100**)

END DEFLECTOR- FULL (**NQD-121-1**)

HARDWARE KIT- **H** CONTENTS:

(2) 5/16 -18 X 1 GR 5 HEX HEAD BOLT

(4) 5/16 SAE **or** 1/4 USS WASHER

(2) 5/16-18 NYLOC NUT

(1) NQD-097-SPRING

(1) SPRING PULLER

REAR HANDLE MOUNT- TORO PRO LINE (**TO-37**)

LINKAGE- **LARGE (NQD-123/124**

NQD-TPL36

TORO PROLINE 2020 AND NEWER 36 INCH DECK



MOUNTING BRACKET HOLE LOCATIONS

STEP 1

REMOVE FACTORY CHUTE.

PLACE QWIKCHUTE ON DECK. CLOSE DOOR ON QWIKCHUTE. CENTER IT UP ON THE DECK OPENING. HOLD DOOR AGAINST THE FACE OF OPENING AND USE HOLES IN MOUNTING BRACKETS AS TEMPLATE MARK HOLES WITH MARKER. REMOVE UNIT CENTER PUNCH AND DRILL TWO 3/8" HOLES. MOUNT QWIKCHUTE TO DECK USING (2) 5/16 X 1 BOLTS WITH WASHERS AND NUTS AS SUPPLIED. HOLD DOOR AGAINST FACE WHEN TIGHTENING HARDWARE.



MOUNTING BOLTS

HANDLE MOUNTING BOLTS




TOOTH WASHERS

HANDLE

STEP 2- REAR HANDLE ASSEMBLY INSTALLATION

1. REMOVE EXISTING BOLTS AND MOUNT ASSEMBLY WITH NEW LONGER BOLTS PROVIDED IN KIT AS SHOWN 3/8-16 X 1-1/4 BOLTS WITH NUTS AND WASHERS)
2. INSTALL HANDLE AS SHOWN WITH SUPPLIED (2) 5/16-18 X 1" BOLTS NUTS AND WASHERS. TOOTH WASHER IS PLACED BETWEEN HANDLE PIVOT BAR AND THE HANDLE. ADJUST TO OPERATORS PREFERENCE.



ROD ENDS

LOCK COLLAR

STEP 3-

INSTALL LINKAGE ROD AS SHOWN TIGHTEN ROD ENDS IN PLACE AND LEAVE THE LOCK COLLAR LOOSE.



PUSH ROD TO BE ADJUSTED AS FOLLOWS:

- A. DECK AT FULL HEIGHT
- B. QWIKCHUTE FULLY CLOSED
- C. HANDLE POSITIONED SO THAT LOWER PORTION OF HANDLE IS 1/2" FROM REAR OF GUIDE PLATE SLOT
- D. TIGHTEN LOCK COLLAR ON CONTROL ROD

STEP 5 -SPRING INSTALL

SPRING INSTALLATION QWIKCHUTE NQD MODEL

STEP 2 LOOP FINGERS OVER SCREWDRIVER
BLADE AND LIFT SPRING ON TO SPRING BOLT
CAUTION --DO NOT OVER STRECH SPRING
DISCARD WIRE LOOP AFTER SPRING IS CONNECTED



HANDLE INSTALLATION AND ADJUSTMENT

QWIKCHUTE OPERATING PRECEDURE

OPEN FULLY- move handle away from operator quickly.

CLOSE FULLY- move handle toward operator quickly.

PARTIALLY OPEN- from close position move handle away from operator until stay bar swings into position and release handle. To close from partially open position, quickly open and then close.

(some models do not have partial open feature.)

OIL ALL BEARING POINTS WEEKLY OR AS NEEDED.

WARRANTY

GTM Manufacturing, Inc. products are warranted to the original purchaser to be free from defects in materials and workmanship for a period of 90 days from the date of purchase.

Any part(s) of GTM products found to be defective within the warranty period shall, at GTM's option, be repaired or replaced without charge.

Warranty consideration is obtained by returning any GTM product/part believed to be defective to GTM Manufacturing, Inc. within the applicable warranty period. **Please call for authorization.**

GTM Manufacturing, Inc.

14350 EASTSIDE ST

GROVELAND, FL. 34736

(407) 654-6598

www.qwikchute.com

Warranty does not apply to conditions resulting from:

1. Damage(s) and/or costs associated with shipping and or/ transportation.
2. Lack of normal maintenance, adjustments, or service required for regular use of the product.
3. Modifications, service/repairs, parts or components not authorized by GTM.

GTM shall not be liable for any special, consequential, direct or indirect damages, and expressly states there are no implied warranties. Some states do not allow limitation of incidental or consequential damages, accordingly the above limitations and exclusions may not apply to you. This warranty provides you with specific legal rights which may vary from state to state.

IT IS THE OWNERS RESPONSIBILITY TO PROPERLY COMPLETE AND MAIL THE WARRANTY REGISTRATION CARD.

PROOF OF PURCHASE AND REGISTRATION WILL BE REQUIRED IN ORDER TO OBTAIN WARRANTY SERVICE.

WARRANTY REGISTRATION CARD

Name of Purchaser: _____

Street Address / P.O. Box: _____

City: _____ State _____ Zip Code: _____

Model Number: _____ PURCHASE DATE: _____|_____|_____

Dealer Name: _____

Street Address: _____

City: _____ State: _____ Zip Code: _____

Customer Received: Operators Manual (☐) Safety Instructions (☐) Demonstration (☐)

Customers Signature

Date